

BrightSign 기능 비교

모델명	HDMI 출력	HDMI 입력	최대 출력해상도	PoE+	SSD	HTML5 렌더링 성능	인터랙티브 입출력	이더넷 속도
XC4055	4	—	8K x 1 / 4K x 4	—	0	★★★★★★★	USB/IR/RS232/ GPIO/UDP	10/100/1000
XC2055	2	—	8K x 1 / 4K x 2	—	0	★★★★★★☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
XT2145	2	1	8K x 1 / 4K x 2	0	0	★★★★★★☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
XT1145	1	1	8K x 1	0	0	★★★★★★☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
XT245	1	—	8K x 1	0	0	★★★★★☆☆	IR/GPIO/UDP	10/100/1000
XD1035	1	—	8K x 1	0	0	★★★★★☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
XD235	1	—	8K x 1	0	0	★★★★★☆☆	IR/GPIO/UDP	10/100/1000
HD1025	1	—	4K x 1	—	—	★★★★☆☆☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
HD225	1	—	4K x 1	—	—	★★★★☆☆☆☆	IR/GPIO/UDP	10/100/1000
LS445	1	—	4K x 1	—	—	★★★☆☆☆☆	USB/UDP	10/100
LS425	1	—	FHD x 1	—	—	★★☆☆☆☆☆☆	USB/UDP	10/100
XD1036	1	—	8K x 1	0	0	★★★★★☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
XD236	1	—	8K x 1	0	0	★★★★★☆☆	IR/GPIO/UDP	10/100/1000
HD1026	1	—	4K x 1	—	—	★★★★☆☆☆☆	USB/IR/RS232/ GPIO/UDP	10/100/1000
HD 226	1	—	4K x 1	—	—	★★★★☆☆☆☆	IR/GPIO/UDP	10/100/1000

